

LIGHTING THE FUTURE "GREENLY"

**L.E.D. lighting is the lighting of the 21st century
It is free from the metals and chemicals used in other
forms of high performance lighting.**



FLOODLIGHTS

We can supply a LED light for

.....

Floodlights

Down lights

Fluero replacements

Festive lighting Etc....

***LED tube retrofits in all sizes
and power output.
These will give the same
brightness for around 60% less
electricity***



LED OFFICE LIGHTING



LED FLOODLIGHTS

***LED FLOOD & STREET
LIGHTS***

***Can be retrofitted into most
existing housings.***

***Power output equivalent from
100 watt to 400 watt with a 77%
Electricity saving AND ...
5 years warranty***

Architectural L.E.D. Panels



NF800-W

Product Features

Parameters	Model (NF800-W)
Dimensions(mm)	Φ800
Weight(kg)	10.2
Input voltage DC(v)	12
Lighting source	LED
Color	Whitelue
Color temperature	6000k-6500k
SuNFace illumination	>=1000LUX
Uniformity of	>=90%
Power	<=25w
The use of ambient temperature	-30℃ /70℃
Life expectancy	>=50000h

The above parameters are for reference only,products with a physical basis,and its size can be based on customer requirements



NF1230

Product Features

Parameters	Model (NF1230)
Dimensions(mm)	1200*300*19
Weight(kg)	5.1
Input voltage DC(v)	12
Lighting source	LED
Color	White
Color temperature	6000k-6500k
SuNFace illumination	>=1000LUX
Uniformity of	>=90%
Power	<=25w
The use of ambient temperature	-30℃ /70℃
Life expectancy	>=50000h

The above parameters are for reference only,products with a physical basis,and its size can be based on customer requirements



Model: 6060

Product Features

Parameters	Model (NF6060)
Dimensions(mm)	600*600*19
Weight(kg)	5.5
Input voltage DC(v)	12
Lighting source	LED
Color	White
Color temperature	6000k-6500k
SuNFace illumination	>=1000LUX
Uniformity of	>=90%
Power	<=25w
The use of ambient temperature	-30℃ /70℃
Life expectancy	>=50000h

The above parameters are for reference only,products with a physical basis,and its size can be based on customer requirements



NF3030

Product Features

Parameters	Model (NF3030)
Dimensions(mm)	300*300*19
Weight(kg)	1.5
Input voltage DC(v)	12
Lighting source	LED
Color	White
Color temperature	6000k-6500k
SuNFace illumination	>=1000LUX
Uniformity of	>=90%
Power	<=8w
The use of ambient temperature	-30℃ /70℃
Life expectancy	>=50000h

The above parameters are for reference only,products with a physical basis,and its size can be based on customer requirements



NF3030

Product Features

Parameters	Model (NF3030)
Dimensions(mm)	300*300*19
Weight(kg)	1.5
Input voltage DC(v)	12
Lighting source	LED
Color	White
Color temperature	6000k-6500k
SuNFace illumination	>=1000LUX
Uniformity of	>=90%
Power	<=8w
The use of ambient temperature	-30℃ /70℃
Life expectancy	>=50000h

The above parameters are for reference only,products with a physical basis,and its size can be based on customer requirements



NF3020-R

Product Features

Parameters	Model (NF3020-R)
Dimensions(mm)	300*200*19
Weight(kg)	1.5
Input voltage DC(v)	12
Lighting source	LED
Color	Red
Color temperature	6000k-6500k
SuNFace illumination	>=1000LUX
Uniformity of	>=90%
Power	<=25w
The use of ambient temperature	-30℃ /70℃
Life expectancy	>=50000h

The above parameters are for reference only,products with a physical basis,and its size can be based on customer requirements